



COMMERCIAL SERIES

TWO STAGE – ELECTRIC – 1 PHASE 208/230 VOLT – NO MAG. STARTER REQUIRED

HP	STAGE	TANK GAL- TYPE	PUMP R.P.M.	C.F.M. @ 0-PSI	C.F.M. @ 100- PSI	LxWxH Dimension	VOLTAGE AMPS	WT. Shipped	UNIT MODEL
5	TWO	80 Vert.	715	21.7	18.1	32x24x74	230/22	560	C518VC1

TWO STAGE PUMP FEATURES:

- *All Cast Iron slow 715 R.P.M. for long life and quite operations.
- *Tapered roller main bearing to provide superior crankshaft support and less friction.
- *Connecting rods have needle bearings at wrist pin and insert bearing at crankshaft.
- *Disc and spring valves for maximum reliability and efficiency.
- *Filter/silencers with paper element provide clean intake air and quite operation.
- *Easy to read sight glass to insure proper oil level at a glance.
- *Centrifugal unloader...for loadless start-up every time.

TANK – MOTOR- CONTROLS

- *Powder coated ASME-tanks with four feet vs. three
- *Rigid metal belt guards.
- *Copper discharge and bleeder tube for strength and increased heat dissipation.
- *Quality American made Baldor motor w/thermal overload protection & a full 15% service factors.

AVAILABLE FACTORY MOUNTED OPTIONS:

- | | | | |
|---------------|---------------------|----------------------------|---------|
| *Auto drains: | #ADVSM air operated | *Dual controls: | #DC1 |
| | #SDV03M electronic | *Beltguard aftercooler: | #BGAC1M |
| *Silencer 1”: | #SA100M | *Right from the start kit: | #RFS001 |