



INDUSTRIAL SERIES

TWO STAGE – ELECTRIC – 1 PHASE 208/230 VOLT – MAG. STARTER MTD.

HP	PHASE	TANK GAL./TYPE	PUMP R.P.M.	CFM@ 0-PSI	CFM@ 175 PSI	LxWxH DIMENSION	Wt. LBS.	UNIT MODEL
5	1	80 vert.	767	22.0	17.5	32x24x74	600	I 518VC1-S

TWO STAGE PUMP FEATURES

- *All Cast Iron slow 767 R.P.M. for long life and quiet operation.
- *Tapered roller bearings at both ends of crankshaft for superior support & less friction.
- *Precision steel connecting rods with automotive type rod insert bearings at crankshaft & needle bearings at wrist pin for long service, life, & reliability.
- *Disc & spring valves for high efficiency and reliability.
- *Centrifugal unloader...for loadless start-up every time.
- *Automotive type intake filter/silencer. *Sight glass to insure proper oil level at a glance.

TANK - MOTOR - CONTROLS

- *Powder coated ASME tank with 4 legs.
- *ASME safety valves. *Metal belt guard totally enclosed.
- *Copper discharge & bleeder tube.
- *Heavy duty industrial motor, 1725 R.P.M. with full 15% service factor.
- *Quality pressure switch & magnetic starter mounted & wired.

AVAILABLE FACTORY MOUNTED OPTIONS:

- | | | | |
|-----------------------|---------|----------------------------|---------|
| * Low oil control | #6304M | * Dual control | #DC1 |
| * Hour meter 230 volt | #HRM75M | * Intake noise silencer | #SA100M |
| * Auto drain | #ADVSM | * Right from the start kit | #RFS001 |
| | #SDV03M | * Beltguard aftercooler | #BGAC1M |