

CASTAIR

COMMERCIAL SERIES

TWO STAGE - ELECTRIC - 1 PHASE 208/230 VOLT - NO MAG. STARTER REQUIRED

UNIT
SPEC'S

HP	Stage	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 100 PSI	LxWxH Dimension	Voltage Amps	Wt. LBS	Unit Model
5	Two	80 vert.	715	21.7	18.1	32x24x74	230/22	560	C518VC1



TWO STAGE PUMP FEATURES:

- All Cast Iron slow 715 RPM for long life and quite operations.
- Tapered roller main bearing to provide superior crankshaft support and less friction.
- Connecting rods have bearings at wrist pin and insert bearing at crankshaft.
- Disc and spring valves for maximum reliability and efficiency.
- Filter/silencers with paper element provide clean intake air and quite operation.
- Easy to read sight glass to insure proper oil level at a glance.
- Centrifugal unloader...for loadless start-up every time.

TANK / MOTOR / CONTROLS:

- Powder coated ASME-tanks with four feet vs. three
- Rigid metal belt guards.
- Copper discharge and bleeder tube for strength and increased heat dissipation.
- Quality American made Baldor motor w/thermal overload protection & a full 15% service factors.
- 30A breaker required for wiring (230V)

AVAILABLE FACTORY MOUNTED OPTIONS:

- Auto Drains: #ADVSM air operated
#SDV03M electronic
- Silencer 1": #SA100M

- Right from the Start Kit: #RFS001
- Dual Control: #DC1
- Beltguard Aftercooler: #BGAC1M