

# CASTAIR

## GARAGE SERIES - ELECTRIC SINGLE STAGE COMPRESSOR

UNIT  
SPEC'S

HP	Stage	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 100 PSI	LxWxH Dimension	Voltage Amps	Wt. LBS	Unit Model
2	SINGLE	20 Port.	1380	10.4	6.5	33x19x30	115/15	175	G212P50



### SINGLE STAGE PUMP FEATURES:

- Cast Iron, slow RPM, oil lubed, belt driven, for quite operation & long life.
- Automotive type filters/silencers with paper element provides clean intake air.
- Easy to read sight glass to insure proper oil level at a glance.
- Smooth running v-twins for 360 deg. cooling around both cylinders.
- Main bearing is automotive type ball bearing for superior crankshaft support.

### UNIT FEATURES:

- Powder coated ASME-tank.
- Rigid metal belt guards.
- Bleeder pressure switch for load-less starts.
- Large 10" tall by 3" wide, never flat semi-pneumatic wheels with steel hubs and dual ball bearings.
- Copper discharge & unloader tube for strength & increased heat dissipation.
- Includes a mounted regulator with gauge & quick coupler.
- Single stage factory set to shut off at 125 PSI.
- 20A outlet required. Never run on an extension cord.