

# CASTAIR

## GARAGE SERIES - ELECTRIC

SINGLE STAGE 208/230V - MOTOR 3450 R.P.M. WITH OVERLOAD PROTECTION - NO MAG. STARTER REQUIRED

UNIT SPEC'S	HP	Stage	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 100 PSI	LxWxH Dimension	Voltage Amps	Wt. LBS	Unit Model
	3.5	SINGLE	60 vert.	1100	18.6	11.5	31x27x70	230/15	250	G3516VS75



### SINGLE STAGE PUMP FEATURES:

- Slow RPM oil lubed.
- Automotive type filter.
- Easy to read sight glass.
- Main bearings are automotive type ball bearings.
- Bleeder pressure switch.

### TANK / MOTOR / CONTROLS:

- Powder coated ASME-tank w/three feet.
- Copper discharge & unloader tube for strength & increased heat dissipation.
- Single stage factory set to shut off at 125 PSI.
- 20A breaker required (230V)
- 3/4" full flow ball valve (standard)

### AVAILABLE FACTORY MOUNTED OPTIONS:

• Auto Drains: #ADVSM air operated  
#SDV03M electronic

• Vibration Pads: #VP1003  
4x4x1 - set of 3