

# CASTAIR

## INDUSTRIAL SERIES TWO STAGE COMPRESSOR

GAS HONDA - 2 STAGE - WITH FUEL TANK

UNIT  
SPEC'S

Honda Model	Starter Type	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 175 PSI	LxWxH Dimension	Wt. LBS	Unit Model
GX390	Rope/Elec.	30 horiz.	635	37.0	30.3	48x22x40	605	I13GH3HC2



### COMPRESSOR PUMP:

- All Cast Iron slow 635 RPM for long life & quiet operation.
- Tapered roller bearings at both ends of crankshaft for superior support & less friction.
- Precision steel connecting rods with automotive type rod insert bearings at crankshaft & bearings at wrist pin for long service life & reliability.
- Disc & spring valves for easy service, maximum reliability & efficiency
- Pistons have 4-rings for higher efficiency & less oil carry-over.
- Automotive type intake air filter/silencer.
- Easy to read sight glass to ensure proper oil level at a glance.

### ENGINE / TANK / CONTROLS:

- Honda Industrial grade engine with 12-volt alternator, rope & electric start & 1.6 gallon fuel tank.
- Pilot valve with built in check valve.
- Copper discharge tube.
- Powder coated ASME tank with channel feet.
- ASME safety valves.
- Rigid metal belt guard totally enclosed.
- Honda oil drain kit mounted.
- Hour meter (optional): #HRM50M
- Right from the Start Kit (optional): #RFS001
- Battery & cables sold separately.