

CASTAIR

INDUSTRIAL SERIES

TWO STAGE - ELECTRIC - 1 PHASE 208/230 VOLT - MAG. STARTER MTD.

UNIT
SPEC'S

HP	Phase	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 175 PSI	LxWxH Dimension	Wt. LBS	Unit Model
5	1	80 vert.	767	22.0	17.5	32x24x74	600	I 518VC1-S



TWO STAGE PUMP FEATURES:

- All Cast Iron slow 767 RPM for long life & quiet operation.
- Tapered roller bearings at both ends of crankshaft for superior support & less friction.
- Precision steel connecting rods with automotive type rod insert bearings at crankshaft & bearings at wrist pin for long service life & reliability.
- Disc & spring valves for easy service, maximum reliability & efficiency.
- Centrifugal unloader...for loadless start-up every time.
- Automotive type intake air filter/silencer.
- Easy to read sight glass to ensure proper oil level at a glance.

TANK / MOTOR / CONTROLS:

- Powder coated USA Made ASME tank with 4 legs.
- ASME safety valves.
- Rigid metal belt guard totally enclosed.
- Copper or stainless braided discharge & bleeder tube.
- Heavy duty industrial Made in America Baldor motor, 1725 RPM with full 15% service factor.
- Quality pressure switch & magnetic starter mounted & wired.
- 30AMP breaker required for wiring. (230V)

AVAILABLE FACTORY MOUNTED OPTIONS:

- | | | |
|---------------------------------|-------------------------------------|----------------------------------|
| • Low oil control: #6304M | • Dual control: #DC1 | • Beltguard aftercooler: #BGAC1M |
| • Hour meter 230 volt: #HRM75M | • Intake noise silencer: #SA100M | • Belt tensioner: #184DM |
| • Auto drain: #ADVSM
#SDV03M | • Right from the start kit: #RFS001 | |