

CASTAIR

GARAGE SERIES – ELECTRIC

SINGLE STAGE 208/230V – MOTOR 3450 R.P.M. WITH OVERLOAD PROTECTION – NO MAG. STARTER REQUIRED

UNIT
SPEC'S

HP	Phase	Tank Gal-Type	Pump RPM	CFM @ 0 PSI	CFM @ 100 PSI	LxWxH Dimension	Voltage Amps	Wt. LBS	Unit Model
3.5	1	60 vert.	1100	18.6	11.5	31x27x70	230/15	250	G3516VS75



SINGLE STAGE PUMP FEATURES:

- Slow RPM oil lubed.
- Automotive type air filter.
- Easy to read sight glass to ensure proper oil level at a glance.
- Main bearings are automotive type ball bearings.

TANK / MOTOR / CONTROLS:

- Powder coated USA Made ASME tank w/three feet.
- Copper discharge & unloader tube.
- Single stage factory set to shut off at 125 PSI.
- Bleeder pressure switch.
- 20AMP breaker required. (230V)
- 3/4" full flow ball valve (standard)

AVAILABLE FACTORY MOUNTED OPTIONS:

• Auto Drains: #ADVSM air operated
#SDV03M electronic

• Vibration Pads: #VP1003
4x4x1 – set of 3